

**Intercommunication System Control
Model A301-1A (C-6533A)****Model A301-1A**

The A301-1A is an upgraded version of Andrea Systems C-6533 product which has been providing reliable service in a variety of helicopters, military and commercial aircraft for almost 40 years. This modernized version boasts a range of new features including digital switching, surface mount technology, and an option to add VOX.

The A301-1A is a single user intercommunication control designed to be the basic unit for an eight user intercommunication system of advanced design.

OPERATING CONTROLS

- Six (6) position rotary selector switch for control of five (5) transmitters / receivers and an Interphone line.
- Seven (7) monitor switches provide for individual selection and mixing of eight (8) audio input lines. (One switch controls two inputs.)
- A Hot Mike switch activates the hot mike function on the interphone line.
- A Master Volume Control permits adjustment of the headset level.

OPTIONAL FEATURES

- Adjustable VOX with ON/OFF.
- A second ICS line (PVT) allows flexible aircraft configurations for a boom operator or other private communications.
- Custom panel markings.
- Transmitter outputs can be preset at the factory to customer specified levels.
- Red, White, or Night Vision lighted panels.
- Embedded lighting in place of lamps.

ADVANCED FEATURES

- Digital switching of audio paths using solid state switches and hardware CPLD controls eliminates mechanical contact noise from the audio path.
- Immediate start-up without software delays.
- EMI and lightning protected.
- Modular construction with plug together boards maximizes internal interconnect reliability.
- Low level or high level mic inputs.
- Supports low impedance (8 ohm, 350 mW) or high impedance (150 ohm, 100 mW) headsets.
- Limited operation down to 10 VDC input voltage for communication during engine start.
- Microphone AGC for consistent talk quality.

READY FOR TODAY'S ENVIRONMENT

- Environmental testing to MIL-E-5400 Class 1
- Lightning including multi-stroke and multi-burst. Tested to A2G22 and A2C3 levels of RTCA DO-160D.
- EMI tested to MIL-STD-461F.

C46-5459 Rev 2

SPECIFICATIONS*

PHYSICAL CHARACTERISTICS

- Size: 5" W x 2 5/8" H x 3 3/4" D
- Weight: 1.85 lbs Max.

ENVIRONMENTAL

- MIL-E-5400 CLASS 1
- Continuous Operating Temperature: -54° C to +55° C
- Intermittent Operating Temperature: +55° C to +71° C
- EMI: MIL-STD-461F
- Lightning: RTCA DO-160D, A2G22 and A2C3

MATING CONNECTOR

- Winchester MRE42SJT6H (not included)

POWER REQUIREMENTS

- Normal Power @ 28 VDC
 - No Signal - 7 W Max.
 - 350 mW Headset Output - 9 W Max.
- Panel Lighting, Standard Configuration with Two Lamps
 - 0.25A @ 27.5 VDC

VOLTAGE LEVELS

- 5 ohm Mic Input: 0.1 to 4.0 mVrms
- High Level Mic Input: 0.1 to 1.0 Vrms
- Headset Output: 1.67 Vrms into 8 ohms,
3.87 Vrms into 150 ohms
- ICS, PVT Interphone Lines: 2.75 Vrms
- Receive Line Inputs: 2.75 Vrms
- Transmitter Outputs: 0 dBm (1 mW = .4 Vrms),
Adjustable+/-3dB

IMPEDANCES

- Microphone Input: 5 ohms (Dynamic Mic) or 200 ohm - 2.2K High Level Mic
- Talk-Out (INT & XMIT): 150 ohms load
- Receiver Input: 150 ohms load
- Headset Output: 8 ohms or 150 ohms load

MICROPHONE AMPLIFIER PERFORMANCE

- Distortion: 3% Max. @ 0.6 mVrms In,
5% Max. @ 4.0 mVrms In.
- Frequency Response: +1/-2 dB 300 to 6000 Hz
- AGC - Maintains constant output for wide variations in input.
 - Breakpoint: 0.2 to 0.5 V applied to the 5000 to 5 ohm pad
 - Attack time: 200 mS Max.
 - Release time: approx. 6 sec.
 - Slope: 3 dB Max. output change for 20 dB input change

* Specifications subject to change without notice.

HEADSET AMPLIFIER PERFORMANCE

- Distortion: 5% Max.
- Frequency Response: +1/-2 dB 300 to 6000 Hz

SIGNAL ISOLATION AT 1KHZ

- Open Monitor Switch: -60 dB minimum
- Audio Input Lines: -60 dB below 50 mW
- Transit Lines: -70 dB below 50 mW
(2.75V)
- Volume Control Range: 28 to 37dB

TALK CAPABILITIES

- Transmitters: Up to 5.
- ICS Lines: One is standard. A PVT interphone line can be added as an option.

MONITOR CAPABILITIES

- Receivers / Audio Inputs: Up to 8. (One toggle switch controls two inputs.)
- 4 Direct Inputs,
 - 2 adjust with volume control
 - 2 have fixed level for alerts or warnings

CONTROLS

- Rotary Switch - 6 position, 5 for transmitters/receivers and one for ICS. As an option a second ICS position can be added for PVT.
- 7 Toggle switches to select audio input lines for monitoring.
- Volume Control for adjustment of the headset level.
- Hot Mike Toggle Switch to activate the Hot Mike function for Interphone. On units where VOX has been added as an option this switch is replaced with a knob to adjust sensitivity.

INTERNAL ADJUSTMENTS

- 5 Individual internal adjustments of the audio output level to each of the five associated transmitters.

ANDREA SYSTEMS LLC

Andrea Systems LLC
140 Finn Court, Farmingdale, New York 11735

PRELIMINARY

www.Andreasystems.com
Phone: (631) 390-3140
Fax: (631) 390-3150